

## Silkolene®

### SILKOLENE PRO KR2

Castor and ester synthetic 2-Stroke engine oil for kart racing

#### Description

SILKOLENE PRO KR2 combines the outstanding wear and load carrying properties of castor oil with clean burning modern synthetics technology, to give exceptional engine performance, sustained power output and reliability.

#### Application

SILKOLENE PRO KR2 is the ideal lubricant for all high output liquid and air-cooled kart engines. It is suitable for use with all gasoline and alcohol fuels. Do **not** mix SILKOLENE PRO KR2 with other lubricants.

For dilution ratios, consult manufacturers recommendations.

#### Advantages

- CIK-FIA Homologated
- Excellent anti-wear protection to engines
- Synthetic fortified castor blend

#### Specifications / Approvals

- SILKOLENE PRO KR2 meets the stringent test requirements of the CIK-FIA (COMMISSION INTERNATIONALE DE KARTING - FEDERATION INTERNATIONALE DE L'AUTOMOBILE) and is a CIK-FIA approved (homologated) lubricant.

## Further Information

### Typical Data: SILKOLENE PRO KR2

Characteristics	Test Method	Unit	
Colour	Visual		Dark orange / Red
SAE Grade			30
Specific Gravity at 15°C	IP160		0.944
Kinematic Viscosity at 40°C	IP71	mm <sup>2</sup> /s	95.9
Kinematic Viscosity at 100°C	IP71	mm <sup>2</sup> /s	11.1
Viscosity Index (VI)	IP226		101
Pour point	IP15	°C	-35
Flash Point (Closed Cup)	IP34	°C	200

Reviewed 21/04/2020 AB